


Description

The DCSDxx-M is designed to replace multilayer varistors (MLVs) in portable applications such as cell phones, notebook computers and PDA's, using monolithic silicon technology to provide fast response time and ultra low ESD clamping voltage, making this device an ideal solution for protecting sensitive semiconductor components from damage. The DCSDxx-M complies with the IEC 61000-4-2 (ESD) standard with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. It is assembled into a lead-free SOD-323 package and will protect one unidirectional line. These devices will fit on the same PCB pad area as an 0805 MLV device.

Mechanical Characteristics

- ◆ Package: SOD-323
- ◆ Lead Finish: Matte Tin
- ◆ Case Material: "Green" Molding Compound.
- ◆ UL Flammability Classification Rating 94V-0
- ◆ Moisture Sensitivity: Level 3 per J-STD-020
- ◆ Terminal Connections: See Diagram Below
- ◆ Marking Information: See Below

Dimensions and Pin Configuration



Circuit and Pin Schematic

Ordering Information

| Part Number | Marking | Packaging | Reel Size |
|-------------|---------|------------------|-----------|
| DCSDxx-M | xxDM | 3000/Tape & Reel | 7 inch |

Features

- ◆ 250W peak pulse power (8/20 μs)
- ◆ Protects one data or power line
- ◆ Ultra low leakage: nA level
- ◆ Operating voltage: 3.3V, 5V, 8V, 12V, 15V, 24V, 36V
- ◆ Ultra low clamping voltage
- ◆ Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC61000-4-4 (EFT) 40A (5/50ns)
- ◆ RoHS Compliant

Applications

- ◆ Cellular Handsets and Accessories
- ◆ Personal Digital Assistants
- ◆ Notebooks and Handhelds
- ◆ Portable Instrumentation
- ◆ Peripherals
- ◆ Pagers Peripherals
- ◆ Desktop and Servers

Marking Information



xxDM = Device Marking Code
xx represents the voltage
Bar denotes Cathode

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Value | Unit |
|---------------------------------|------------------|-------------|------|
| ESD per IEC 61000-4-2 (Air) | V _{ESD} | ±30 | kV |
| ESD per IEC 61000-4-2 (Contact) | | ±30 | |
| Operating Temperature Range | T _J | -55 to +125 | °C |
| Storage Temperature Range | T _{stg} | -55 to +150 | °C |

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

| DCSD03-M (Marking Code: 03DM) | | | | | | |
|-------------------------------|------------------|-----|-----|-----|------|--|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | V _{RWM} | | | 3.3 | V | |
| Breakdown Voltage | V _{BR} | 4 | | | V | I _T = 1mA |
| Reverse Leakage Current | I _R | | | 0.5 | μA | V _{RWM} = 3.3V |
| Forward Voltage | V _F | | 0.8 | 1.2 | V | I _F = 10mA |
| Clamping Voltage | V _C | | 5 | | V | I _{PP} = 1A (8 x 20μs pulse) |
| Clamping Voltage | V _C | | 10 | | V | I _{PP} = 18A (8 x 20μs pulse) |
| Peak Pulse Current | I _{PP} | | | 18 | A | t _p = 8/20μs |
| Junction Capacitance | C _J | | | 90 | pF | V _R = 0V, f = 1MHz |

| DCSD05-M (Marking Code: 05DM) | | | | | | |
|-------------------------------|-----------|-----|-----|-----|---------------|--|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | V_{RWM} | | | 5 | V | |
| Breakdown Voltage | V_{BR} | 6 | | | V | $I_T = 1\text{mA}$ |
| Reverse Leakage Current | I_R | | | 0.5 | μA | $V_{RWM} = 5\text{V}$ |
| Forward Voltage | V_F | | 0.8 | 1.2 | V | $I_F = 10\text{mA}$ |
| Clamping Voltage | V_C | | 7 | | V | $I_{PP} = 1\text{A}$ (8 x 20 μs pulse) |
| Clamping Voltage | V_C | | 11 | | V | $I_{PP} = 16\text{A}$ (8 x 20 μs pulse) |
| Peak Pulse Current | I_{PP} | | | 16 | A | $t_p = 8/20\mu\text{s}$ |
| Junction Capacitance | C_J | | | 85 | pF | $V_R = 0\text{V}$, $f = 1\text{MHz}$ |

| DCSD08-M (Marking Code: 08DM) | | | | | | |
|-------------------------------|-----------|-----|-----|-----|---------------|--|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | V_{RWM} | | | 8 | V | |
| Breakdown Voltage | V_{BR} | 8.5 | | | V | $I_T = 1\text{mA}$ |
| Reverse Leakage Current | I_R | | | 0.5 | μA | $V_{RWM} = 8\text{V}$ |
| Forward Voltage | V_F | | 0.8 | 1.2 | V | $I_F = 10\text{mA}$ |
| Clamping Voltage | V_C | | 10 | | V | $I_{PP} = 1\text{A}$ (8 x 20 μs pulse) |
| Clamping Voltage | V_C | | 15 | | V | $I_{PP} = 13\text{A}$ (8 x 20 μs pulse) |
| Peak Pulse Current | I_{PP} | | | 13 | A | $t_p = 8/20\mu\text{s}$ |
| Junction Capacitance | C_J | | | 70 | pF | $V_R = 0\text{V}$, $f = 1\text{MHz}$ |


| DCSD12-M (Marking Code: 12DM) | | | | | | |
|-------------------------------|-----------|------|-----|-----|---------------|--|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | V_{RWM} | | | 12 | V | |
| Breakdown Voltage | V_{BR} | 13.3 | | | V | $I_T = 1\text{mA}$ |
| Reverse Leakage Current | I_R | | | 0.5 | μA | $V_{RWM} = 12\text{V}$ |
| Forward Voltage | V_F | | 0.8 | 1.2 | V | $I_F = 10\text{mA}$ |
| Clamping Voltage | V_C | | 15 | | V | $I_{PP} = 1\text{A}$ (8 x 20 μs pulse) |
| Clamping Voltage | V_C | | 24 | | V | $I_{PP} = 10\text{A}$ (8 x 20 μs pulse) |
| Peak Pulse Current | I_{PP} | | | 10 | A | $t_p = 8/20\mu\text{s}$ |
| Junction Capacitance | C_J | | | 40 | pF | $V_R = 0\text{V}$, $f = 1\text{MHz}$ |

| DCSD15-M (Marking Code: 15DM) | | | | | | |
|-------------------------------|-----------|------|-----|-----|---------------|---|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | V_{RWM} | | | 15 | V | |
| Breakdown Voltage | V_{BR} | 16.7 | | | V | $I_T = 1\text{mA}$ |
| Reverse Leakage Current | I_R | | | 0.5 | μA | $V_{RWM} = 15\text{V}$ |
| Forward Voltage | V_F | | 0.8 | 1.2 | V | $I_F = 10\text{mA}$ |
| Clamping Voltage | V_C | | 20 | | V | $I_{PP} = 1\text{A}$ (8 x 20 μs pulse) |
| Clamping Voltage | V_C | | 30 | | V | $I_{PP} = 8\text{A}$ (8 x 20 μs pulse) |
| Peak Pulse Current | I_{PP} | | | 8 | A | $t_p = 8/20\mu\text{s}$ |
| Junction Capacitance | C_J | | | 30 | pF | $V_R = 0\text{V}$, $f = 1\text{MHz}$ |


| DCSD24-M (Marking Code: 24DM) | | | | | | |
|-------------------------------|-----------------|------|-----|-----|------|---|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | VRWM | | | 24 | V | |
| Breakdown Voltage | VBR | 26.7 | | | V | IT = 1mA |
| Reverse Leakage Current | IR | | | 0.5 | μA | VRWM = 24V |
| Forward Voltage | VF | | 0.8 | 1.2 | V | IF=10mA |
| Clamping Voltage | VC | | 33 | | V | I _{PP} = 1A (8 x 20μs pulse) |
| Clamping Voltage | VC | | 45 | | V | I _{PP} = 3.5A (8 x 20μs pulse) |
| Peak Pulse Current | I _{PP} | | | 3.5 | A | tp=8/20μs |
| Junction Capacitance | CJ | | | 15 | pF | VR = 0V, f = 1MHz |

| DCSD36-M (Marking Code: 36DM) | | | | | | |
|-------------------------------|-----------------|-----|-----|-----|------|---------------------------------------|
| Parameter | Symbol | Min | Typ | Max | Unit | Test Condition |
| Reverse Working Voltage | VRWM | | | 36 | V | |
| Breakdown Voltage | VBR | 40 | | | V | IT = 1mA |
| Reverse Leakage Current | IR | | | 0.5 | μA | VRWM = 36V |
| Forward Voltage | VF | | 0.8 | 1.2 | V | IF=10mA |
| Clamping Voltage | VC | | 41 | | V | I _{PP} = 1A (8 x 20μs pulse) |
| Clamping Voltage | VC | | 60 | | V | I _{PP} = 2A (8 x 20μs pulse) |
| Peak Pulse Current | I _{PP} | | | 2 | A | tp=8/20μs |
| Junction Capacitance | CJ | | | 10 | pF | VR = 0V, f = 1MHz |


Typical Performance Characteristics (TA=25°C unless otherwise Specified)




8 X 20μs Pulse Waveform



Peak Pulse Power vs. Pulse Time




Note: Data is taken with a 10x attenuator
ESD Clamping Voltage
8 kV Contact per IEC61000-4-2




Power Derating Curve

SOD-323 Package Outline Drawing



| SYM | DIMENSIONS | | | |
|-----|-------------|------|--------|-------|
| | MILLIMETERS | | INCHES | |
| | MIN | MAX | MIN | MAX |
| A | 1.50 | 1.80 | 0.060 | 0.071 |
| B | 1.20 | 1.40 | 0.045 | 0.054 |
| C | 2.30 | 2.70 | 0.090 | 0.107 |
| D | - | 1.10 | - | 0.043 |
| E | 0.30 | 0.40 | 0.012 | 0.016 |
| F | 0.10 | 0.25 | 0.004 | 0.010 |
| H | - | 0.10 | - | 0.004 |

Suggested Land Pattern



| SYM | DIMENSIONS | |
|-----|-------------|--------|
| | MILLIMETERS | INCHES |
| A | 3.15 | 0.120 |
| B | 0.80 | 0.031 |
| C | 0.80 | 0.031 |

Contact Information

Changzhou D-first Electronics CO.,Ltd.

www.first-electronic.com

Email: xhf@first-electronic.cn

Phone: +86 (0519) 8817 1671